



NOTES:

1. ALL LOT SERVICE LATERALS TO BE INSTALLED PRIOR TO PAVING OF STREET, INCLUDING FIRE SPRINKLER PREVENTION SERVICE.
2. 1.5' WHEN SIDEWALK IS ADJACENT TO R/W.
3. WHEN ABUTTING SOIL HAS A HIGH SULFATE CONTENT, USE A MODIFIED CONCRETE MIX AND PLACE 6" MIN CLASS 2 AGGREGATE BASE AND 6 MIL PLASTIC SHEETING UNDER AND AROUND ALL SIDES OF CONCRETE IMPROVEMENTS. FOR EXPANSIVE SOIL, PLACE 6" MIN CLASS 2 AGGREGATE BASE UNDER CONCRETE IMPROVEMENTS AS DIRECTED BY THE ENGINEER. SEE SPECIFICATIONS SECTIONS 16.03 & 16.04 AND STANDARD No. 401 FOR REFERENCE.

NOT TO SCALE

PREPARED UNDER THE SUPERVISION OF:

Mark Lancaster

11/30/22
DATE

DIRECTOR OF TRANSPORTATION
MARK LANCASTER, P.E.



COUNTY OF RIVERSIDE

**WATER METER
INSTALLATION**

STANDARD No. 700

REVISION	DESCRIPTION	MARK	DATE	APPROVED