



NOTE:  
 REQUIREMENT PER COUNTY PLAN  
 CHECK POLICIES AND GUIDELINES:  
 MINIMUM FALL AROUND CUL-DE-SACS  
 SHALL BE 1.0% MINIMUM, HOWEVER  
 A 0.5% MINIMUM IS ALLOWED WITH  
 PRIOR APPROVAL.

OFFSET MAY BE LOCATED  
 EITHER LEFT OR RIGHT.

NOT TO SCALE

R/W	CURVE 1					CURVE 2				CURVE 3								
	A	B	C	D	E	△	FL		R/W		△	CROWN						
							R	L	R	L		R	L					
50'	25'	16'	9'	116.19'	32.00'	29°39' 31"	109'	56.42'	100'	51.76'	209°39' 31"	38'	139.05'	47'	171.98'	29°39' 31"	170.14'	88.07'
56'	28'	18'	10'	112.87'	31.44'	27°35' 48"	110'	52.98'	100'	48.17'	207°35' 48"	38'	137.68'	48'	173.92'	27°35' 47"	175.79'	84.67'
60'	30'	20'	10'	108.90'	29.45'	25°31' 48"	110'	49.01'	100'	44.56'	205°31' 48"	38'	136.31'	48'	172.18'	25°31' 48"	184.35'	82.14'
66'	33'	22'	11'	104.94'	27.47'	23°20' 19"	111'	45.21'	100'	40.73'	203°20' 19"	38'	134.86'	49'	173.90'	23°20' 19"	195.54'	79.65'
74'	37'	22'	15'	106.15'	28.08'	23°09' 45"	115'	46.49'	100'	40.43'	203°09' 45"	38'	134.74'	53'	187.93'	23°09' 45"	198.48'	80.24'
78'	39'	28'	11'	121.38'	35.69'	28°47' 56"	111'	55.79'	100'	50.26'	208°47' 56"	50'	182.21'	61'	222.30'	28°47' 56"	177.87'	89.41'
SCHEDULE "H"						CURVE 1 - EDGE OF AB				CURVE 2 - EDGE OF AB				CURVE 4 - EDGE OF AB				
-	-	12'	-	113.58'	31.79'	31°24' 45"	98.05'	55.47'	-	-	215°36' 50"	38'	143.00'	-	-	4°12' 05"	831.70'	60.99'

PREPARED UNDER THE SUPERVISION OF:

*Mark Lancaster*

11/30/22  
DATE

DIRECTOR OF TRANSPORTATION  
 MARK LANCASTER, P.E.



COUNTY OF RIVERSIDE

**OFFSET  
 CUL-DE-SAC**

**STANDARD No. 800A**

REVISION	DESCRIPTION	MARK	DATE	APPROVED